# **OSRAM**

## NIGHT BREAKER LED SMART H7

#### NIGHT BREAKER LED SMART H7





Street-Legal 1

The NIGHT BREAKER LED family - OSRAM's first street-legal1) LED retrofit lamps.



Up to 330% more brightness2) & 6000K

See and be seen with OSRAM. Cool white color temperature similar to daylight. For more safety on the road, especially when driving at night



Up to 6 times longer lifetime3)

Vibration resistant, environmentally friendly, and cost-efficient



#### 5 Year OSRAM Guarantee4)

Systematic quality assurance measures underpin the premium workmanship and functionality of our products. Innovative technology and excellent quality really pay dividends for our customers.



Exceptionally bright, innovatively compact, widely applicable, broadly compatible, particularly durable and, of course, street-legal1) That's the new NIGHT BREAKER LED SMART from OSRAM.

Experience the next milestone from OSRAM and discover completely new terrain in the world of street-legal1) LED retrofit lamps with the NIGHT BREAKER LED SMART from OSRAM. The new highlight from OSRAM for automotive and vehicle enthusiasts and of course for everyone else. This new highlight from OSRAM raises vision & visibility, durability & compatibility, reliability & safety to the next level.OSRAM's street-legal1) LED lamps set new standards in terms of innovation, precision, versatility and functionality. They lead the way in terms of brightness, lifetime, vehicle compatibility, design and much more. With the street-legal 1) NIGHT BREAKER LED SMART, its innovative compact design, sophisticated construction and exceptional brightness, it is now possible to switch from traditional halogen lamps to advanced OSRAM LED technology in even more vehicles5). With the street-legal1) NIGHT BREAKER LED SMART you can now upgrade the function of your high- and low beam lights of your vehicle to state-of-the-art LED technology. These LED replacement lamps are suitable as a replacement for conventional lamps and bases. They offer a modern and bright white light with a color temperature of up to 6000 Kelvin and impress with up to 330% more brightness2), while the glare of other road users falls below the permissible maximum values by up to 50%2). In comparison to standard lamps, such as halogen lamps, these LED retrofit lamps consume up to 60% less energy and convince thanks to the LED technology and the specially developed vibrationresistant design, with up to 6 times longer life time3). You can now replace your conventional vehicle lamps with OSRAM's revolutionary NIGHT BREAKER LED retrofit lamps and experience trend-setting brightness with road approval1) Additionally, OSRAM offers a dedicated guarantee on all NIGHT BREAKER LED retrofit lamps2)

#### Technical data

## **Product information**

| Product legal advice 1                      | 1) Approved LED light source - only applies to the respective countries in which there is approval or to which an equivalent approval applies and the vehicle models and light functions currently listed in the compatibility list. For more details see www.osram.com/nb-led |
|---|--|
| Product legal advice 2                      | 2) In comparison to the minimum requirements of ECE R112, while the glare is below the maximum permissible values by up to 50%   |
| Product legal advice 3                      | 3) In comparison to traditional Halogen lamps  |
| Product legal advice 4                      | 4) For precise conditions please refer to: www.osram.com/am-guarantee  |
| Application (Category and Product specific) | High and low beam  |

## **General Product Information**

| Global order reference | 64210DWNBSM-2HB |
|------------------------|-----------------|
|                        |                 |


## **Electrical Data**

| Power input           | 16.0 W |
|-----------------------|--------|
| Test voltage          | 13.2 V |
| Power input tolerance | ±10 %  |
| Nominal wattage       | 16 W   |
| Nominal voltage       | 12.0 V |

## **Photometric Data**

| Color temperature       | 6000 K     |
|-------------------------|------------|
| Nominal luminous flux   | 1550 lm    |
| Luminous flux tolerance | ±10 %      |
| Light color LED         | Cool white |

## **Physical Attributes & Dimensions**



| Product weight | 52.00 g |
|----------------|---------|
| Length         | 71.0 mm |

#### **Lifetime Data**

| Lifespan Tc | 3000 hr |
|-------------|---------|
| Lifespan B3 | 1500 hr |

## **Capabilities**

| Technology | LED |
|------------|-----|

#### Certificates & standards

| <b>Standards</b> ABG |
|----------------------|
|----------------------|

## **Environmental & Regulatory Information**

| Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh) |               |  |  |
|---|---------------|--|--|
| Primary article identifier  | 4062172408332 |  |  |
| Declaration no. in SCIP database                                      | l arbete      |  |  |

#### Logistical Data

| Product code  | Product description           | Packaging unit<br>(Pieces/Unit) | Dimensions (length x width x height) | Volume               | Gross weight |
|---------------|-------------------------------|---------------------------------|--------------------------------------|----------------------|--------------|
| 4062172408332 | NIGHT BREAKER<br>SMART H7 LED | HFB<br>2                        | 136 mm x 56 mm x<br>162 mm           | 1.23 dm <sup>3</sup> | 209.00 g     |
| 4062172408349 | NIGHT BREAKER<br>SMART H7 LED | Shipping carton box 4           | 149 mm x 125 mm x<br>180 mm          | 3.35 dm <sup>3</sup> | 501.00 g     |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

#### Safety advice

Application advice: For more detailed application information and graphics please see product datasheet and user manual.

#### Legal advice

1) Approved LED light source - only applies to the respective countries in which there is approval or to which an equivalent approval applies and the vehicle models and light functions currently listed in the compatibility list. For more details see www.osram.com/nb-led2)Compared to the minimum requirements of ECE R112, while the glare is below the maximum permissible values by up to 50%3) In comparison to traditional Halogen lamps4) For precise conditions please refer to: www.osram.com/am-guarantee5) In comparison to the previous versions of NIGHT BREAKER LEDs

#### **Application advice**

For more detailed application information and graphics please see product datasheet.

#### **Disclaimer**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.



